



Address: 8 Manburgh Terrace,
Darra 4076
Postal P.O. Box 3045
Address: Darra Qld. 4076
Phone: +61 (7) 3375 3199
Facsimile: +61 (7) 3375 3886
E-mail: info@luxurypaints.com.au
Date Issued: 9 July, 2019

LP0003

NON DRIP CEILING

Product Line: 13

Product Code: 1301; 1302; 1304; 1310; 1315.

Australian Paint Approval Scheme: 0260/5

Description

A premium quality, interior, flat white water based ceiling paint designed for outstanding hiding power. The special 'non drip' formulation enables ease of application with minimal amount of splatter.

Special features include

Water based rapid drying, flat finish with non-drip, non-splatter formulation. Easy to apply, excellent adhesion, flow and quick drying (same day recoat).

Uses

Suitable for use on all interior ceilings where a flat finish is desired. PLEASE NOTE: the flatter the finish, the harder to remove marks etc. Allow the surface to fully cure about 7 days before attempting to carefully remove any soil marks. Do not use Non Drip Ceiling White in areas that are subject to steam and condensation or areas that require constant washing.

Typical Specifications

Surface	Preparation	System	Dry Film Thickness
Plasterboard (New condition)	Fill joints etc and sand. Remove dust.	First Coat: Speed-prep Sealer Undercoat Top Coat: 2 coats Non Drip Ceiling	25 - 30µm 50 - 60µm
Plasterboard (Previously painted)	Treat mould/ mildew if present. Alternatively wash ceiling if contaminants present. Allow to dry.	Top Coat: 2 coats Non Drip Ceiling	50 - 60µm

Surface Preparation

All surfaces must be well prepared and free from dirt, oil, grease and other contaminants.

NEW UNPAINTED SURFACES

Fill any surface imperfections with appropriate patching material. Sand and dust area ensuring the surface is clean and dust free. Seal surface by applying 1 coat of Speed-prep Sealer Undercoat. Allow to dry before applying 2 coats of Non Drip Ceiling White. (For best results, we recommend 2 coats).

PREVIOUSLY PAINTED SURFACES

Ensure surface is clean. Remove any loose and flaking paint. Chalked surfaces must be rubbed and washed down. Glossy surfaces must be sanded to reduce gloss in order to enable adequate adhesion. Treat any mould/ mildew affected areas with chlorine bleach or propriety mould/ mildew treatment product used according to label instructions and allow to dry. Seal bare areas with appropriate sealer and apply 2 coats of Non Drip Ceiling White.

Application Method

Stir contents of can thoroughly with a wide flat stirrer ensuring the bottom of the can is reached. Apply full even coats of Non Drip Ceiling White by brush, roller or spray.

Do not apply Non Drip Ceiling White below 12°C or is likely to fall below 12°C, before the paint can through dry.



Address: 8 Manburgh Terrace,
Darra 4076
Postal P.O. Box 3045
Address: Darra Qld. 4076
Phone: +61 (7) 3375 3199
Facsimile: +61 (7) 3375 3886
E-mail: info@luxurypaints.com.au
Date Issued: 9 July, 2019

LP0003

Brush/Roller

Pre-wet brushes and rollers. Flow paint generously and spread evenly. (Do not overspread). For the best results, use a quality bristle brush or a medium 12mm nap roller cover on smooth surfaces or a 20mm long nap cover on semi-rough surfaces. Apply one full even coat. Avoid excessive brushing as this will introduce brush-marks.

Spray

May be sprayed by airless or conventional spray. Use a 13 thou tip for airless spray application.

Thinning

Not usually required, however it may be thinned sparingly with water.

Approximate Coverage

Covers approximately 12 -16 square metres per litre depending on the surface porosity.

Available in 1, 2, 4 & 15 litres.

Colours Available

Available in white which may be tinted to a limited range of colours.

Drying Times

Approximate drying times at 25°C and 50% Relative Humidity.

Touch Dry:	30 minutes
Recoat:	Minimum 2 hours.

Drying Times may be extended by adverse drying conditions or very high film build.

Cleanup

Clean all equipment promptly with water.

Properties

SOLIDS BY VOLUME:	33%
SOLIDS BY WEIGHT:	53%
WEIGHT PER LITRE:	1.45kg
GLOSS LEVEL:	FLAT (less than 2 gloss units)
VOC:	approximately 52 g/litre

Resistance Properties

ABRASION:	Poor
HEAT:	Good. May soften at elevated temperatures.
SOLVENT:	Poor. Coating is sensitive to aromatic hydrocarbons, alcohols and ketones.
WATER/STEAM:	Poor. Not recommended.
WEATHER:	For interior use only.

Additional Information

The flatter the finish, the more difficult to remove soil marks. Avoid excessive scrubbing to prevent patchiness. Non Drip Ceiling White is slightly shaded to enable maximum opacity and evenness of appearance.