



SAFETY DATA SHEET

TIMBERCLEAR TUFF

Date Issued: 09 June, 2015

NON - HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

1. Identification of the substance/ preparation and the company

TIMBERCLEAR TUFF

Product Line: 122

Product Code: 12201; 12204; 12210.

Application:

Brushing, spraying grade of architectural water based acrylic coloured clear timber coating.

| | | | |
|-----------------|---|------------|--|
| Supplier: | Luxury Paints Pty Ltd | ABN | 85 465 041 603 |
| Address: | 8 Manburgh Terrace, Darra, Brisbane Qld, 4076 Australia | | |
| Postal Address: | PO Box 3045 Darra Qld, 4076 Australia | | |
| Contact: | Telephone: +61 (7) 3375 3199 | A/H: mob.: | 0413 949 709 |
| | Fax: +61 (7) 3375 3886 | Email: | info@luxurypaints.com.au |

2. Hazards identification

Health Hazard Classification

This product is classified as non-hazardous under NOHSC criteria.

Hazard Category

Not applicable. Sanding of the coating may release particles of dust which is classified as 'nuisance dust'.

Risk Phrases

R36/37/38 Irritating to eyes, respiratory system and skin.

R65 Harmful: May cause lung damage if swallowed.

Safety Phrases

S2 Keep out of the reach of children.

S3/7/9 Keep container tightly closed in a cool, well ventilated place.

S24/25 Avoid contact with skin and eyes.

Dangerous Goods Classification

Not applicable.

Poisons Schedule

Not applicable.

3. Composition: Information on Ingredients

| Ingredient | CAS No. | Proportion % v/v |
|--------------------------------------|---------------|------------------|
| Acrylic co-polymer emulsion | Not regulated | 30 - ≤ 60 |
| Pigments – non-hazardous | Various | 1 - ≤ 30 |
| Propylene glycol | 57-55-6 | 1 - ≤ 10 |
| Preservative – non formaldehyde type | | 1 - ≤ 10 |
| Additives | Various | < 5 |
| Water | 7732-18-5 | Remainder |



SAFETY DATA SHEET TIMBERCLEAR TUFF

Date Issued: 09 June, 2015

| |
|--|
| <p>4. First Aid Measures</p> <p>For advice, contact Poisons Information Centre (Phone Australia: 1311 26) or a doctor.</p> <p>Ingestion If swallowed, and if more than 15 minutes from a hospital or medical centre induce vomiting preferably using Ipecac Syrup APF. Keep at rest. Seek immediate medical attention. DO NOT INDUCE VOMITING IN AN UNCONSCIOUS PERSON.</p> <p>Eye Contact Flush eyes with large amounts of water until irritation subsides. Seek immediate medical attention.</p> <p>Skin Contact Wash affected with soap and water or suitable skin cleansing cream. Remove contaminated clothing, including shoes, and launder before reuse. Seek immediate medical attention.</p> <p>Inhalation Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Seek immediate medical attention.</p> <p>First Aid facilities Provide eye baths and safety showers.</p> <p>Medical Attention Treat according to symptoms.</p> |
| <p>5. Fire Fighting Measures</p> <p>Shut off product that may 'fuel' a fire if safe to do so. Allow trained personnel to attend a fire in progress, providing fire-fighters with this Material Safety Data Sheet. Prevent extinguishing media from escaping to drains and waterways. NOTE: This product is not flammable unless strongly heated in an existing fire.</p> <p>Suitable extinguishing media Water.</p> <p>Hazardous products from combustion Carbon dioxide and carbon monoxide.</p> <p>Precautions for fire fighters and special protective equipment Full protective clothing and self-contained breathing apparatus.</p> <p>Hazchem Code None.</p> |
| <p>6. Accidental Release Measures</p> <p>Emergency Procedures Prevent fluid from escaping to drains and waterways. Contain leaking packaging in a containment drum or dam constructed of inert material e.g. sand or other approved material. Prevent vapours from building up in confined areas. Ensure that drain valves are closed at all times. Clean up and report spills immediately.</p> <p>Methods and materials for containment</p> <p>Major Land Spill</p> <ul style="list-style-type: none"> • Prevent liquid from entering sewers, watercourses or low lying areas. • Keep the public away from the area. <p>6. Advise authorities if substance has entered a watercourse or sewer or has contaminated</p> |



SAFETY DATA SHEET TIMBERCLEAR TUFF

Date Issued: 09 June, 2015

Accidental Release Measures (continued)

- soil or vegetation.

Major Land Spill (continued)

- Take measures to minimise the effect on ground water.
- Contain the spill with sand or earth.
- Recover by pumping – use pump or hand pump – or with suitable absorbent material.
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- See “First Aid Measure” and “Stability and Reactivity” sections.

Major Water Spill

- Notify the port or relevant authority and keep the public away from the area.
- Shut off the source of the spill if possible and safe to do so.
- Confine the spill if possible.
- Remove the product from the surface by skimming or with suitable absorbent material.
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- See “First Aid Measure” and “Stability and Reactivity” sections.

7. Handling and Storage

Precautions for safe handling

This product is non -flammable. Keep container closed. Handle containers with care. Open slowly to control possible pressure release.

Conditions for safe storage

Store in a cool, dry place away from direct sunlight. Keep out of the reach of children.

Incompatible materials

Acids, Oxidising Agents or Chemicals

8. Exposure Controls: Personal Protection

National Exposure Standards

The time weighted average concentration (TWA) for this product is: None specified - which means the highest allowable exposure concentration in an eight-hour day for a five-day working week. The short-term exposure limit (STEL) is: None specified, which is the maximum allowable exposure concentration at any time.

Biological limit values

None established.

Engineering Controls: Ventilation

The use of local exhaust ventilation is recommended to control process emissions near the source. Laboratory samples should be handled in a fume hood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

Personal Protective Equipment

Respiratory Protection

Where concentrations in air may exceed the limits described in the National Exposure Standards, it is

Recommended to use a half-face filter mask to protect from overexposure by inhalation. A type ‘A’ filter material is considered suitable for this product. It is recommended that a suitable dust mask and eye protection are worn when sanding the dried film of paint coating.

Eye protection

Always use safety glasses or a face shield when handling this product.

(to be continued)



SAFETY DATA SHEET TIMBERCLEAR TUFF

Date Issued: 09 June, 2015

| <p>8. Exposure Controls: Personal Protection (continued) Personal Protective Equipment (Skin/ Body Protection) Always wear long sleeves and long trousers or coveralls, and enclosed footwear or safety boots when handling this product. It is recommended that chemical resistant gloves be worn when using this product.</p> <p>Protection and hygienic measures Keep away from foodstuffs, drinks and tobacco. Wash hands before breaks and at the end of work. Keep working clothes separate. Take off immediately any contaminated clothing.</p> <p>Flammability Product is non-flammable. However it will burn when strongly heated in an existing fire.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---------------------|---------------------|---------------|------------|---|-----------------|----------------------|----|-------------|-------------|----|---------------|----------------|-------|------------|------------------------|-----|-------|------------------------------|---|----------------|-----------------------|-----|---------------|---------------------------|----|----------------|------------------|---------|----------|--------------------------|---|---------|---------------------|-------|----------|
| <p>9. Physical and chemical properties</p> <table border="1"> <thead> <tr> <th>Property</th> <th>Unit of measurement</th> <th>Typical value</th> </tr> </thead> <tbody> <tr> <td>Appearance</td> <td>-</td> <td>Coloured liquid</td> </tr> <tr> <td>Boiling Point/ Range</td> <td>°C</td> <td>100 (Water)</td> </tr> <tr> <td>Flash point</td> <td>°C</td> <td>Non-flammable</td> </tr> <tr> <td>Density @ 25°C</td> <td>g/ ml</td> <td>1.00 – 1.2</td> </tr> <tr> <td>Vapour Pressure @ 20°C</td> <td>kPa</td> <td>Water</td> </tr> <tr> <td>Explosive Limits (LEL – UEL)</td> <td>%</td> <td>Not applicable</td> </tr> <tr> <td>Vapour Density @ 20°C</td> <td>kPa</td> <td>Not available</td> </tr> <tr> <td>Auto-ignition Temperature</td> <td>°C</td> <td>Not applicable</td> </tr> <tr> <td>Viscosity @ 25°C</td> <td>Seconds</td> <td>55 - 100</td> </tr> <tr> <td>Percent Solids by weight</td> <td>%</td> <td>35 – 45</td> </tr> <tr> <td>Solubility in water</td> <td>% w/w</td> <td>Miscible</td> </tr> </tbody> </table> <p>Remarks: The values for density and viscosity are guide values.</p> | Property | Unit of measurement | Typical value | Appearance | - | Coloured liquid | Boiling Point/ Range | °C | 100 (Water) | Flash point | °C | Non-flammable | Density @ 25°C | g/ ml | 1.00 – 1.2 | Vapour Pressure @ 20°C | kPa | Water | Explosive Limits (LEL – UEL) | % | Not applicable | Vapour Density @ 20°C | kPa | Not available | Auto-ignition Temperature | °C | Not applicable | Viscosity @ 25°C | Seconds | 55 - 100 | Percent Solids by weight | % | 35 – 45 | Solubility in water | % w/w | Miscible |
| Property | Unit of measurement | Typical value | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Appearance | - | Coloured liquid | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Boiling Point/ Range | °C | 100 (Water) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Flash point | °C | Non-flammable | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Density @ 25°C | g/ ml | 1.00 – 1.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Vapour Pressure @ 20°C | kPa | Water | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Explosive Limits (LEL – UEL) | % | Not applicable | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Vapour Density @ 20°C | kPa | Not available | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Auto-ignition Temperature | °C | Not applicable | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Viscosity @ 25°C | Seconds | 55 - 100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Percent Solids by weight | % | 35 – 45 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Solubility in water | % w/w | Miscible | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>10. Stability and reactivity Chemical stability Stable under normal conditions of use.</p> <p>Conditions to avoid Sources of heat and ignition, open flames.</p> <p>Hazardous decomposition products No hazardous decomposition products when stored and handled correctly except on burning. See "Fire Fighting Measures".</p> <p>Hazardous reactions: Oxidizing agents, mineral acids, halogenated organic compounds.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>11. Toxicological information Health Effects: Acute: Swallowed: May cause irritation to the throat, mouth and digestive tract. Large doses may cause drowsiness and may lead to unconsciousness. Aspiration of liquid into lungs may cause serious (even fatal) pneumonitis.</p> <p style="text-align: right;">(Continued on next page)</p> <p>Eye: Irritant, both by contact and vapour.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



SAFETY DATA SHEET TIMBERCLEAR TUFF

Date Issued: 09 June, 2015

| | |
|--|---|
| <p>Skin:</p> <p>Inhaled:</p> <p>Chronic:</p> <p>Advice to Doctor:</p> | <p>Irritant, both by contact and vapour. Prolonged exposure may result in dryness and cracking.</p> <p>Vapour is irritating to mucous membranes and respiratory tract. Can cause dizziness, headaches, nausea and may lead to unconsciousness. Prolonged exposure to vapour may cause damage to the central nervous system.</p> <p>Principal routes of exposure are usually by skin contact with the material and inhalation of vapour/ spray mist. Prolonged or repeated skin contact may cause drying and/or cracking with irritation and possible dermatitis following. As with any chemical product, contact with unprotected bare skin; inhalation of vapours, mist or dust in a work place environment; or ingestion in any form should be avoided by observing good occupational work practices.</p> <p>Treat symptomically.</p> |
| <p>12. Ecological information</p> <p>Aquatic Toxicity</p> <p>Fish Toxicity (rainbow trout, goldfish, and bluegill)</p> <p>LC₅₀ (96 hr):</p> <p>Daphnia Magna EC₅₀ (48 hr):</p> <p>Remark:</p> <p>Do not allow to escape into waterways, waste water or soil.</p> | <p>Based on data for similar components or preparations, this product is expected to be toxic to aquatic organisms.</p> <p>Long term adverse effects to aquatic organisms are possible if continuous exposure is maintained.</p> <p>On the basis of the data for ecotoxicological effects, the substance can be classified as non-critical to aquatic organisms in the water-soluble range. As the substance is not readily biodegradable, long retention times in water are to be expected. This applies only in cases where no other elimination mechanisms (photodegradation, hydrolysis, adsorption) are active. However, as there is no ecotoxic effect, no damage to the ecosystem is to be expected.</p> |
| <p>13. Disposal considerations</p> | <p>The relevant local, regional and national regulations must be complied with. It is among the tasks of the polluter to assign the waste to waste codes specific to industrial sectors and processes according to the national authority. It is recommended that details be worked out with the waste disposal company responsible.</p> <p>The waste can be disposed of in a suitable incinerator or approved landfill site, provided that national/ local legislation is complied with.</p> <p>For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.</p> <p>After final product withdrawal, all residues must be removed from containers (drip-free, powder-free or paste-free). Once the product residues adhering to the walls of the containers have been rendered harmless, the product and hazard labels must be invalidated. Containers must be recycled in compliance with national and environmental regulations</p> |



SAFETY DATA SHEET TIMBERCLEAR TUFF

Date Issued: 09 June, 2015

| | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--------------------|-------------------------------|--|--------|-------------|----------|-----|-----------|-------------|----------|-----|---------------|-----------------|-------------|--|-------|-------------|----------|-----|---------------|-------------|----------|------|--------------------|-------------|----------|--|
| 14. | Transport information | <p>Non-hazardous Good according to ADG Code (7th Edition) Hazchem: None</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 33%;">GGVSE:</td> <td style="width: 33%;">UN No: None</td> <td style="width: 33%;">PG: None</td> <td style="width: 15%;">SP:</td> </tr> <tr> <td>RID/ ADR:</td> <td>UN No: None</td> <td>PG: None</td> <td>SP:</td> </tr> <tr> <td>Warning sign:</td> <td>Hazard No. None</td> <td>UN No. None</td> <td></td> </tr> <tr> <td>ADNR:</td> <td>UN No: None</td> <td>PG: None</td> <td>SP:</td> </tr> <tr> <td>GGVSee/ IMDG:</td> <td>UN No: None</td> <td>PG: None</td> <td>MPO:</td> </tr> <tr> <td>ICAO-TI/ IATA-DGR:</td> <td>UN No: None</td> <td>PG: None</td> <td></td> </tr> </table> <p>Declaration for land shipment: PAINT Declaration for sea shipment: PAINT Declaration for shipment by air: PAINT</p> <p>Limited quantity regulations applicable in accordance with chapter 3.4 RID/ ADR in compliance with threshold value.</p> <p>Other information: Keep dry. Keep separated from foodstuffs.</p> | GGVSE: | UN No: None | PG: None | SP: | RID/ ADR: | UN No: None | PG: None | SP: | Warning sign: | Hazard No. None | UN No. None | | ADNR: | UN No: None | PG: None | SP: | GGVSee/ IMDG: | UN No: None | PG: None | MPO: | ICAO-TI/ IATA-DGR: | UN No: None | PG: None | |
| GGVSE: | UN No: None | PG: None | SP: | | | | | | | | | | | | | | | | | | | | | | | |
| RID/ ADR: | UN No: None | PG: None | SP: | | | | | | | | | | | | | | | | | | | | | | | |
| Warning sign: | Hazard No. None | UN No. None | | | | | | | | | | | | | | | | | | | | | | | | |
| ADNR: | UN No: None | PG: None | SP: | | | | | | | | | | | | | | | | | | | | | | | |
| GGVSee/ IMDG: | UN No: None | PG: None | MPO: | | | | | | | | | | | | | | | | | | | | | | | |
| ICAO-TI/ IATA-DGR: | UN No: None | PG: None | | | | | | | | | | | | | | | | | | | | | | | | |
| 15. | Regulatory Information | <p>Not a scheduled poison under SUSDP. Labeling as required by Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP3), in accordance with Australian requirements. Symbol: Xi, Hazard description: Irritant</p> <p>R22 Harmful if swallowed. R36/37/38 Irritating to eyes, respiratory system and skin. R65 Harmful: May cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness and cracking. R67 Vapours may cause drowsiness and dizziness. S2 Keep out the reach of children. S3/7/9 Keep container tightly closed in a cool, well ventilated place. S24/25 Avoid contact with skin and eyes. S51 Use only in well ventilated areas. S62 If swallowed, and more than 15 minutes from hospital or a medical centre induce vomiting: seek medical advice immediately and show this container or label.</p> | | | | | | | | | | | | | | | | | | | | | | | | |
| | Other information | <p>All components of this product are listed in the European Inventory of Existing Commercial Substances (EINECS) under the provisions laid down in the corresponding EC-Directive. The components are also listed in the Australia Inventory of Chemical Substances (NICNAS).</p> <p>Text of all R-phrases referred to in Sections 2 and 3: R 36: Irritating to the eyes. R 38: Irritating to the skin. R 36/ 37/ 38: Irritating to the eyes, respiratory system and skin.</p> <p>This Safety Data Sheet replaces all previous information. Revised and valid from: see Date of Issue.</p> | | | | | | | | | | | | | | | | | | | | | | | | |

The data given here is based on current knowledge and experience. The purpose of this Material Safety Data Sheet is to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance.

End of Report.