



1. IDENTIFICATION OF THE MATERIAL SUPPLIER

1.1 Product Identifier

Product Name: EASI SPRAY METAL PRIMER
Product Line: 61
Product Code: 61XX01, 61XX04, 61XX20

1.2 Uses and uses advised against

Uses(s) METAL PRIMER • PAINT

1.3 Details of the supplier of the product

Supplier Name LUXURY PAINTS PTY LTD
Address 8 Manburgh Terrace, Darra, QLD, 4076, AUSTRALIA
Telephone (07) 3375 3199
Fax (07) 3375 3886
Email info@luxurypaints.com.au

Website <http://www.luxurypaints.com.au>

1.4 Emergency telephone number(s)

Emergency (07) 3375 3199; 0413 949 709 (After Hours)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

Flammable Liquids Category 3
Acute Toxicity – Oral Category 4
Acute Toxicity – Dermal Category 4
Acute Toxicity–Inhalation Category 4
Skin Corrosion/Irritation Category 2
Skin sensitisation Category 1A
Specific Target Organ Toxicity on Single Exposure: Category 3

2.2 Label elements

Signal word WARNING

Pictogram(s)



Hazard statement(s)

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H313 May be harmful in contact with skin.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements for Prevention:

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements for Responses:

P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin water/shower.
P304 + P340	Call a POISON CENTER or doctor/physician if you feel unwell.
P312	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment is advised - see first aid instructions.
P330	Rinse mouth.
P313 + P3332+P337	If skin or eye irritation occurs: Get medical advice/ attention.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use appropriate media for extinction.

Precautionary statements for storage:

P235, 403	Store in a well ventilated place. Keep cool.
P405	Store locked up

Precautionary Statement for disposal:

P501	Dispose off contents /container in accordance with local, regional, national and international regulations.
------	---

2.3 Other Hazards

Poisons Schedule Australia: S5 (Caution)

3. COMPOSITION/ INFORMATION OF INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Weight %
ALKYD RESIN(S)	Not Available	Not Available	20 to 30
LOW AROMATIC WHITE SPIRIT(S)	64742-82-1	-	1 to 3
XYLENE	1330-20-7	215-535-7	30 to 40
METHYL ETHYL KETOXIME	96-29-7	202-496-6	<1
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold lids apart and flush continuously with running water. Seek medical attention without delay.
Inhalation	Remove from contaminated area. Apply artificial respiration if not breathing. Do not give direct mouth-to-mouth resuscitation. To protect rescuer, use air-viva, oxy-viva or one-way mask.

Resuscitate in a well-ventilated area. Seek medical attention immediately.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Seek medical attention if there is irritation.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Rinse mouth with water.

First aid facilities Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special Hazards arising from the substance or mixture

Flammable. May evolve carbon oxides and hydrocarbons when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, pilot lights, heaters, naked lights, mobile phones, etc when handling. Earth containers when dispensing fluids.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use water fog to cool intact containers and nearby storage areas

5.4 Hazchem code

● 3Y

● 3 Alcohol Resistant Foam is the preferred firefighting medium but, if it is not available, normal foam can be used.

Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with absorbent material (sawdust, vermiculite, sand or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Observe good personal hygiene, including washing hands before eating. Prohibit eating and drinking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store tightly sealed in a cool, dry, well-ventilated area, removed from heat and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards	TWA		STEL		Reference
Ingredient	ppm	mg/m ³	ppm	mg/m ³	
Xylene	80		150		From solvent SDS

Biological limits

Ingredient	Determinant	Sampling Time	BEI
XYLENE	Methyl hippuric acids in urine	End of shift	1.5 g/g creatinine

Reference: ACGIH Biological Exposure Indices

8.2 Exposure controls

Engineering controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

PPE

B OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES

Eyes / Face

Wear splash-proof goggles.

Hands

Wear PVA or Viton (R) gloves.

Body

Wear coveralls

Respiratory

If spraying, wear a Type A-ClassP1 (Organic gases/vapours and Particulate) respirator or an Air-line respirator. If sanding dry product, wear a Class P1 (Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	COLOURED LIQUID
Odour	SLIGHT ODOUR
Flammability	FLAMMABLE
Flash point	31°C
Boiling point	145°C to 190°C
Melting point	NOT APPLICABLE
Evaporation rate	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Specific gravity ⁰	1.25 to 1.40
Solubility (water)	INSOLUBLE
Vapour pressure	0.429 kPa @ 20°C
Upper explosion limit	7.0 %
Lower explosion limit	0.6 %

Autoignition temperature	> 200°C
Decomposition temperature	NOT AVAILABLE
Viscosity	> 450 cSt @ 25°C
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
% Volatiles	32 % to 38 %

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources. Incompatible with Natural rubber, Butyl Rubber and Polystyrene.

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Information available for the product:

Harmful if swallowed. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, fatigue, dizziness and unconsciousness.

Information available for the ingredient(s):

Ingredient	Oral Toxicity (LD50)	Dermal Toxicity (LD50)	Inhalation Toxicity (LC50)
XYLENE	4300 mg/kg (rat)	> 1700 mg/kg (rabbit)	4330–5984 ppm/6 hours
METHYL ETHYL KETOXIME	930 mg/kg (rat)	200 uL/kg (rabbit)	--

Skin	Contact may result in drying and defatting of the skin, rash and dermatitis.
Eye	Contact may result in irritation, lacrimation, pain and redness.
Sensitisation	May cause an allergic skin reaction. This product is not classified as a respiratory sensitiser.
Mutagenicity	Not classified as a mutagen.
Carcinogenicity	Not classified as a carcinogen.
Reproductive	Over exposure to toluene may damage fertility or the unborn child.
STOT-single exposure	Over exposure may result in irritation of the nose and throat, coughing, nausea and headache. High level exposure may result in dizziness, drowsiness, breathing difficulties and unconsciousness.
STOT-repeated exposure	Repeated exposure to toluene may result in central nervous system (CNS), liver and kidney damage.
Aspiration	This product does not present an aspiration hazard.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Based on data for similar components or preparations, this product is expected to be toxic to aquatic organisms. Long term adverse effects to aquatic organisms are possible if continuous exposure is maintained.

12.2 Persistence and degradability

As the substance is not readily biodegradable, long retention times in water are to be expected. This applies only in cases where no other elimination mechanisms (photo degradation, hydrolysis, and adsorption) are active. However, as there is no eco-toxic effect, no damage to the ecosystem is to be expected.

12.3 Bioaccumulative potential No information available.

12.4 Mobility in soil No information available.

12.5 Other adverse effects Do not allow to escape into waterways, waste water or soil.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information if disposing of large quantities (if required). Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1263	1263	1263
14.2 Proper Shipping Name	PAINT or PAINT RELATED MATERIAL	PAINT or PAINT RELATED MATERIAL	PAINT or PAINT RELATED MATERIAL
14.3 Transport Hazard Class	3	3	3
14.4 Packing Group	III	III	III

14.5 Environmental hazards Hydrocarbon solvents in the product are classified as Marine Pollutants.

14.6 Special precautions for user

Hazchem code •3Y

GTEPG 3C1

EMS F-E, S-E

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

Hazard codes

F	Flammable
Xi	Irritant
Xn	Harmful

Risk phrases

R10	Flammable.
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R37	Irritating to respiratory system.
R43	May cause sensitisation by skin contact.
R67	Vapours may cause drowsiness and dizziness.

Safety phrases

S16	Keep away from sources of ignition - No smoking.
S24	Avoid contact with skin.
S28	After contact with skin, wash immediately with plenty of water.
S62	If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Inventory listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS or are exempt.

16. OTHER INFORMATION

The information contained in this data sheet is based on current knowledge and experience. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Luxury Paints, and to recommend precautionary measures for the storage and handling of the product.

This Safety Data Sheet replaces all previous information.

The above details do not imply any guarantee concerning composition, properties or performance.

Reason for revision: Re-checking alignment to GHS.

Revised and valid from: see Date of Issue.

References: Raw Material Data Sheets

https://cfpub.epa.gov/ecotox/quick_query.htm, <http://chem.sis.nlm.nih.gov/chemidplus>

Globally Harmonized System of Classification and Labelling of Chemicals (GHS). Fourth Revised Edition.

United Nations. New York and Geneva, 2011.

Abbreviations:

ADG Code	The Australian Dangerous Goods for the Transport of Dangerous Goods by Road and Rail
AICS	Australia Inventory of Chemical Substances
CAS Number	Chemical Abstract Service Number. Unique for each chemical.
BEI	Biological Exposure Index
EC No	European Community Number
EPA	Environmental Protection Agency
GHS	Globally Harmonised System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Concentration
mg/cm³	milligram per cubic metre
OEL	Occupational Exposure Limit
ppm	Parts per million
STEL	Short Term Exposure Limit
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average