



---

## 1. IDENTIFICATION OF THE MATERIAL SUPPLIER

---

### 1.1 Product Identifier

Product Name: HAMMER FINISH  
Product Code: 69 Series  
Product Line: 69XX04, 69XX20, where XX represents digits for colour codes.

### 1.2 Uses and uses advised against

Uses(s) GLOSS HAMMER FINISH PAINT • SOLVENT BASED. PAINT  
Spraying grade of enamel paint with hammer finish

### 1.3 Details of the supplier of the product

Supplier Name LUXURY PAINTS PTY LTD  
Address 8 Manburgh Terrace, Darra, QLD, 4076, AUSTRALIA  
Telephone (07) 3375 3199  
Fax (07) 3375 3886  
Email [info@luxurypaints.com.au](mailto:info@luxurypaints.com.au)  
Website <http://www.luxurypaints.com.au>

### 1.4 Emergency telephone number(s)

Emergency (07) 3375 3199; 0413 949 709 (After Hours)

---

## 2. HAZARDS IDENTIFICATION

---

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

GHS classification(s) Flammable Liquids: Category 3  
Acute Toxicity: Oral: Category 4  
Skin Sensitisation: Category 1A  
Specific Target Organ Systemic Toxicity (Single Exposure): Category 3  
Aquatic Toxicity (Chronic): Category 3

### 2.2 Label elements

Signal word **WARNING**

Pictogram(s)



Hazard statement(s)

H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

HAMMER FINISH SDS

SDS Date: 5 February, 2026  
Version 3

**Precautionary Statements for Prevention:**

|      |                                                                            |
|------|----------------------------------------------------------------------------|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. No smoking.           |
| P233 | Keep container tightly closed.                                             |
| P240 | Ground/bond container and receiving equipment.                             |
| P241 | Use explosion-proof electrical/ventilating/lighting equipment.             |
| P243 | Take precautionary measures against static discharge.                      |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray.                          |
| P264 | Wash thoroughly after handling.                                            |
| P270 | Do not eat, drink or smoke when using this product.                        |
| P271 | Use only outdoors or in a well-ventilated area.                            |
| P272 | Contaminated work clothing should not be allowed out of the workplace.     |
| P273 | Avoid release to the environment.                                          |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |

**Precautionary Statements for Responses:**

|                    |                                                                                                                                  |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------|
| P303 + P361 + P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin water/shower.                            |
| P304 + P340        | Call a POISON CENTER or doctor/physician if you feel unwell.                                                                     |
| P312               | IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.                                        |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P321               | Specific treatment is advised - see first aid instructions.                                                                      |
| P330               | Rinse mouth.                                                                                                                     |
| P313 + P3332+P337  | If skin or eye irritation occurs: Get medical advice/ attention.                                                                 |
| P363               | Wash contaminated clothing before reuse.                                                                                         |
| P370 + P378        | In case of fire: Use appropriate media for extinction.                                                                           |

**Precautionary statements for storage:**

|           |                                              |
|-----------|----------------------------------------------|
| P235, 403 | Store in a well ventilated place. Keep cool. |
| P405      | Store locked up                              |

**Precautionary Statement for disposal:**

|      |                                                                                                             |
|------|-------------------------------------------------------------------------------------------------------------|
| P501 | Dispose off contents /container in accordance with local, regional, national and international regulations. |
|------|-------------------------------------------------------------------------------------------------------------|

**2.3 Other Hazards**

Poisons Schedule Australia: S5 (Caution)

---

## 3. COMPOSITION/ INFORMATION OF INGREDIENTS

---

**3.1 Substances / Mixtures**

| Ingredient                | CAS Number    | EC Number     | Weight %  |
|---------------------------|---------------|---------------|-----------|
| ALKYD RESIN(S)            | Not Available | Not Available | 37 to 45  |
| XYLENE                    | 1330-20-7     | 215-535-7     | 58 to 62  |
| METHYL ETHYL KETOXIME     | 96-29-7       | 202-496-6     | <1        |
| NON HAZARDOUS INGREDIENTS | Not Available | Not Available | Remainder |

---

## 4. FIRST AID MEASURES

---

**4.1 Description of first aid measures**

|            |                                                                                                                                                                                                                                                                       |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye        | If in eyes, hold lids apart and flush continuously with running water. Seek medical attention without delay.                                                                                                                                                          |
| Inhalation | Remove from contaminated area. Apply artificial respiration if not breathing. Do not give direct mouth-to-mouth resuscitation. To protect rescuer, use air-viva, oxy-viva or one-way mask. Resuscitate in a well-ventilated area. Seek medical attention immediately. |

|                      |                                                                                                                                                                    |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Skin                 | If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Seek medical attention if there is irritation.            |
| Ingestion            | For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Rinse mouth with water. |
| First aid facilities | Eye wash facilities and safety shower should be available.                                                                                                         |

#### **4.2 Most important symptoms and effects, both acute and delayed**

See Section 11 for more detailed information on health effects and symptoms.

#### **4.3 Immediate medical attention and special treatment needed**

Treat symptomatically.

---

## **5. FIRE FIGHTING MEASURES**

---

### **5.1 Extinguishing media**

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

### **5.2 Special Hazards arising from the substance or mixture**

Flammable. May evolve carbon oxides and hydrocarbons when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, pilot lights, heaters, naked lights, mobile phones, etc when handling. Earth containers when dispensing fluids.

### **5.3 Advice for firefighters**

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use water fog to cool intact containers and nearby storage areas

### **5.4 Hazchem code**

- 3Y
- 3     Alcohol Resistant Foam is the preferred firefighting medium but, if it is not available, normal foam can be used.
- Y     Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

---

## **6. ACCIDENTAL RELEASE MEASURES**

---

### **6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Contact emergency services where appropriate.

### **6.2 Environmental precautions**

Prevent product from entering drains and waterways.

### **6.3 Methods of cleaning up**

Contain spillage, then cover / absorb spill with absorbent material (sawdust, vermiculite, sand or similar), collect and place in suitable containers for disposal.

### **6.4 Reference to other sections**

See sections 8 and 13 for exposure controls and disposal.

---

## **7. HANDLING AND STORAGE**

---

### **7.1 Precautions for safe handling**

Observe good personal hygiene, including washing hands before eating. Prohibit eating and drinking in contaminated areas.

Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

### **7.2 Conditions for safe storage, including any incompatibilities**

Store tightly sealed in a cool, dry, well-ventilated area, removed from heat and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

| Exposure standards | TWA |                   | STEL |                   | Reference        |
|--------------------|-----|-------------------|------|-------------------|------------------|
| Ingredient         | ppm | mg/m <sup>3</sup> | ppm  | mg/m <sup>3</sup> |                  |
| Xylene             | 80  |                   | 150  |                   | From solvent SDS |

### Biological limits

| Ingredient | Determinant                    | Sampling Time | BEI                |
|------------|--------------------------------|---------------|--------------------|
| XYLENE     | Methyl hippuric acids in urine | End of shift  | 1.5 g/g creatinine |

### 8.2 Exposure controls

|                      |                                                                                                                                                                                                                                                                                                                                                                                           |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engineering controls | Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard. |
| PPE                  | B OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES                                                                                                                                                                                                                                                                                                                                          |
| Eyes / Face          | Wear splash-proof goggles.                                                                                                                                                                                                                                                                                                                                                                |
| Hands                | Wear PVA or Viton (R) gloves.                                                                                                                                                                                                                                                                                                                                                             |
| Body                 | Wear coveralls                                                                                                                                                                                                                                                                                                                                                                            |
| Respiratory          | If spraying, wear a Type A-ClassP1 (Organic gases/vapours and Particulate) respirator or an Air-line respirator. If sanding dry product, wear a Class P1 (Particulate) respirator.                                                                                                                                                                                                        |



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|                               |                  |
|-------------------------------|------------------|
| Appearance                    | COLOURED LIQUID  |
| Odour                         | SLIGHT ODOUR     |
| Flammability                  | FLAMMABLE        |
| Flash point                   | 31°C             |
| Boiling point                 | 145°C to 190°C   |
| Specific gravity <sub>0</sub> | 0.95 to 1.03     |
| Solubility (water)            | INSOLUBLE        |
| Vapour pressure               | 0.429 kPa @ 20°C |
| Upper explosion limit         | 7.0 %            |
| Lower explosion limit         | 0.6 %            |
| Autoignition temperature      | > 200°C          |
| Decomposition temperature     | NOT AVAILABLE    |

|                      |                  |
|----------------------|------------------|
| Viscosity            | > 450 cSt @ 25°C |
| Explosive properties | NOT AVAILABLE    |
| Oxidising properties | NOT AVAILABLE    |
| % Volatiles          | 55 % to 62 %     |

## 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

No normal reactivity concern as per the information available from raw material data.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Hazardous polymerization is not expected to occur.

### 10.4 Conditions to avoid

Avoid contact with food. Avoid exposure to frost, excess heat and open flames.

### 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid).

### 10.6 Hazardous decomposition products

### 10.6 Hazardous decomposition products

Will evolve hydrocarbons when heated and will evolve carbon monoxide and dioxide when heated to decomposition.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

#### Acute toxicity

#### Information available for the product:

Harmful if swallowed. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, fatigue, dizziness and unconsciousness.

#### Information available for the ingredient(s):

| Ingredient            | Oral Toxicity (LD50) | Dermal Toxicity (LD50) | Inhalation Toxicity (LC50) |
|-----------------------|----------------------|------------------------|----------------------------|
| XYLENE                | 4300 mg/kg (rat)     | > 1700 mg/kg (rabbit)  | 4330–5984 ppm/6 hours      |
| METHYL ETHYL KETOXIME | 930 mg/kg (rat)      | 200 uL/kg (rabbit)     | --                         |

#### Skin

Contact may result in drying and defatting of the skin, rash and dermatitis. This product is classified as a Category 2 Hazard. Causes skin irritation.

#### Eye

Contact may result in irritation, lacrimation, pain and redness.

#### Sensitisation

May cause an allergic skin reaction. This product is not classified as a respiratory sensitiser.

#### Mutagenicity

Insufficient data available to classify as a mutagen.

#### Carcinogenicity

Insufficient data available to classify as a carcinogen.

#### Reproductive

Insufficient data available to classify as a reproductive toxin.

#### STOT-single exposure

May cause respiratory irritation. Over exposure may result in irritation of the nose and throat, coughing, nausea and headache. High level exposure may result in dizziness, drowsiness, breathing difficulties and unconsciousness.

#### STOT-repeated exposure

Repeated exposure to some solvents have been reported to cause adverse effects to the central nervous system (CNS), liver and kidney.

#### Aspiration

Aspiration into the lungs may cause chemical pneumonitis and pulmonary oedema.

## 12. ECOLOGICAL INFORMATION

**12.1 Toxicity:** Harmful to aquatic life with long lasting effects.

**12.2 Persistence and degradability** This product is not readily biodegradable.

**12.3 Bioaccumulative potential:** No information available.

**12.4 Mobility in soil:** No information available.

### 12.5 Other adverse effects

Aliphatic hydrocarbons behave differently in the environment depending on their size. WATER: Light aliphatics volatilise rapidly from water (half life - few hours). Bioconcentration should not be significant. SOIL: Light aliphatics biodegrade quickly in soil and water, heavy aliphatics biodegrade very slowly. ATMOSPHERE: Vapour-phase aliphatics will degrade by reaction with hydroxyl radicals.

## 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Waste disposal For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site.

Contact the manufacturer/supplier for additional information if disposing of large quantities (if required).

Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

Legislation Dispose off in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



|                             | LAND TRANSPORT (ADG)            | SEA TRANSPORT (IMDG / IMO)      | AIR TRANSPORT (IATA / ICAO)     |
|-----------------------------|---------------------------------|---------------------------------|---------------------------------|
| 14.1 UN Number              | 1263                            | 1263                            | 1263                            |
| 14.2 Proper Shipping Name   | PAINT or PAINT RELATED MATERIAL | PAINT or PAINT RELATED MATERIAL | PAINT or PAINT RELATED MATERIAL |
| 14.3 Transport Hazard Class | 3                               | 3                               | 3                               |
| 14.4 Packing Group          | III                             | III                             | III                             |

14.5 Environmental hazards Hydrocarbon solvents in the product are classified as Marine Pollutants.

14.6 Special precautions for user

Hazchem code •3Y

GTEPG 3C1

EMS F-E, S-E

## 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Poison schedule** Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications** Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

|                      |                                                                                                                |
|----------------------|----------------------------------------------------------------------------------------------------------------|
| Hazard codes         |                                                                                                                |
| F                    | Flammable                                                                                                      |
| Xi                   | Irritant                                                                                                       |
| Xn                   | Harmful                                                                                                        |
| Risk phrases         |                                                                                                                |
| R10                  | Flammable.                                                                                                     |
| R20/21/22            | Harmful by inhalation, in contact with skin and if swallowed.                                                  |
| R37                  | Irritating to respiratory system.                                                                              |
| R43                  | May cause sensitisation by skin contact.                                                                       |
| R67                  | Vapours may cause drowsiness and dizziness.                                                                    |
| Safety phrases       |                                                                                                                |
| S16                  | Keep away from sources of ignition - No smoking.                                                               |
| S24                  | Avoid contact with skin.                                                                                       |
| S28                  | After contact with skin, wash immediately with plenty of water.                                                |
| Inventory listing(s) | AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS or are exempt. |

## 16. OTHER INFORMATION

The information contained in this data sheet is based on current knowledge and experience. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Luxury Paints, and to recommend precautionary measures for the storage and handling of the product.

This Safety Data Sheet replaces all previous information.

The above details do not imply any guarantee concerning composition, properties or performance.

Reason for revision: Re-checking alignment to GHS.  
Revised and valid from: see Date of Issue.

References:

Raw Material Data Sheets

[https://cfpub.epa.gov/ecotox/quick\\_query.htm](https://cfpub.epa.gov/ecotox/quick_query.htm)

<http://chem.sis.nlm.nih.gov/chemidplus>

Globally Harmonized System of Classification and Labelling of Chemicals (GHS). Fourth Revised Edition.

United Nations. New York and Geneva, 2011

### Abbreviations:

|                          |                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------|
| <b>ADG Code</b>          | The Australian Dangerous Goods for the Transport of Dangerous Goods by Road and Rail |
| <b>AICS</b>              | Australia Inventory of Chemical Substances                                           |
| <b>CAS Number</b>        | Chemical Abstract Service Number. Unique for each chemical.                          |
| <b>BEI</b>               | Biological Exposure Index                                                            |
| <b>EC No</b>             | European Community Number                                                            |
| <b>EPA</b>               | Environmental Protection Agency                                                      |
| <b>GHS</b>               | Globally Harmonised System                                                           |
| <b>GTEPG</b>             | Group Text Emergency Procedure Guide                                                 |
| <b>IARC</b>              | International Agency for Research on Cancer                                          |
| <b>LC50</b>              | Lethal Concentration, 50% / Median Lethal Concentration                              |
| <b>LD50</b>              | Lethal Dose, 50% / Median Lethal Concentration                                       |
| <b>mg/cm<sup>3</sup></b> | milligram per cubic metre                                                            |
| <b>OEL</b>               | Occupational Exposure Limit                                                          |
| <b>ppm</b>               | Parts per million                                                                    |
| <b>STEL</b>              | Short Term Exposure Limit                                                            |
| <b>SUSMP</b>             | Standard for the Uniform Scheduling of Medicines and Poisons                         |
| <b>TSCA</b>              | Toxic Substances Control Act                                                         |
| <b>TWA</b>               | Time Weighted Average                                                                |